

# CK610060GT18

## Electrical Characteristics

Material	Permeability ( $\mu$ )	AL $\pm$ 8% (nH/N <sup>2</sup> )	DCB (% min) @ 100 Oe	Coreloss (mW/cm <sup>2</sup> , max) @ 50kHz, 300G
Mega Flux GT	60	138	72.8	47

OD : 610



## Core Dimensions

Dimensions		Uncoated		Coated		Color	Packaging
		(mm)	(inch)	(mm)	(inch)		
OD	(Max)	62.00	2.441	63.10	2.484	Black	Box Qty = 24 pcs
ID	(min)	32.60	1.283	31.37	1.235		
HT	(max)	18.00	0.709	19.00	0.748		

## Physical Characteristics

Cross Section (A)	Path Length ( $l$ )	Window Area (Wa)	Volume (V)	Breakdown Voltage (Vac)
2.646 cm <sup>2</sup>	14.37 cm	7.73 cm <sup>2</sup>	38.023 cm <sup>3</sup>	1,000
0.4101 in <sup>2</sup>	5.66 in	1,525,558 cmil	2.3202 in <sup>3</sup>	

## Winding Information

0% Winding length/turn (cm)		
6.973		
40% winding factor Surface Area (cm <sup>2</sup> )		
153.13		
40% Wound Di.(mm)		
OD	ID	HT
70.78	20.54	28.26

## Typical DC Bias Performance

